



PVCu Solvent Cleaner

Revision: 11/04/2019 Page 1 from 1

Technical data

Basis	Solvent mixture
Consistency	Fluid
Density	Ca. 0,90 g/ml
Flashpoint	< 20 °C
Application temperature	5 °C → 25 °C

^{*} These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

PVCu Solvent Cleaner is a highly effective, fast acting, non-smear, liquid cleaning agent suitable for removing ingrained dirt and marks on white or veneered PVCu frames and other plastics.

Properties

- Fast acting
- Fast drying
- Ready to use (no mixing required)
- Non-smearing
- Restores to a clear and shiny finish
- Perfumed
- Multi-purpose use
- Non-abrasive
- Highly flammable

Applications

- Cleaning of most types of white and veneered PVCu frames, sills, cladding, panels and trims.
- For removing most ingrained dirt, grease, uncured sealant, pencil and pen mark.
- Cleaning of plastic garden furniture.

Packaging

Colour: colourless Packaging: 1 L bottle

Shelf life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrates

Substrates: white or veneered PVCu window

frames, hard PVC Nature: dirty.

Surface preparation: No pretreatment required.

Application method

Application method: For best results, apply and spread PVCu Solvent Cleaner onto surface with a clean, soft, colourfast cloth or paper tissue, working well into the surface. Leave to rest for a few minutes. (About 15 min.) Wipe away contamination and then polish the cleaned surface using a second dry cloth or paper tissue. Always work with a clean cloth to avoid contamination of the surface. Always wipe in one direction.

Health- and Safety Recommendations

Consult label and material safety data sheet for more information. Take the usual labour hygiene into account. Use only in well-ventilated areas. Always wear gloves and goggles. After contact with skin rinse immediately with soap and water. Ingestion: rinse off the mouth with running water avoiding ingesting the liquid. Get in touch with a doctor. The user has to check if the product is suitable for the specific application.

Remarks

- It is recommended to do a compatibility test prior to application.
- Do not dilute product.

Remark: This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

 Soudal NV
 Everdongenlaan 18 - 20
 B-2300 Turnhout, Belgium

 Tel: +32 (0)14-42.42.31
 Fax: +32 (0)14-42.65.14
 www.soudal.com