THE FOLLOWING SALT SPRAY TEST REPORT APPLIES TO ALL TIMCO WINDOW SCREWS WITH A ZINC & CLEAR PASSIVATED FINISH.



MOXLEY INDUSTRIAL CENTRE **WESTERN WAY** WEDNESBURY **WEST MIDLANDS** WS10 7BG

TEL: 0121 505 4050 FAX: 0121 505 1115

www.rotechlabs.co.uk info@rotechlabs.co.uk



Test Report

Our Ref: GBW

Number

162554-1

Issue

Date 07/12/2016 Page

1 of

A/C No: M114

Tested For:-

T I MIDWOOD & COMPANY LIMITED

Green Lane Wardle Nantwich Cheshire CW5 6BJ

### SALT SPRAY TESTING OF TIMCO 3.9 x 25mm WINDOW SCREW SAMPLES

#### INTRODUCTION

The finished samples were submitted to the laboratory for Salt Spray Corrosion Resistance Testing in accordance with the relevant specification.

# RELEVANT INFORMATION

Description:

20 off. Timco 3.9 x 25mm S/Drill PVC Screw CSK BZP

Samples

Finish:

Zinc Plated & Clear Passivate

TIMco Code:

123Z

Batch No.

5055017528240

Specification:

Salt Spray Test in accordance with BS EN ISO 9227:2012

Test Duration:

240 Hours Salt Spray Exposure

Submitted By:

Cris Tonks

Customer's Order No:

5277CT

Sample Receipt Date:

24/11/2016

## RESULTS

## Salt Spray Test (BS EN ISO 9227:2012)

The samples were exposed to a neutral 5% Salt Spray, for a test period of 240 hours.

Examination after every 24 hours revealed the following observations:-

24 - 240 Hours

The samples showed no evidence of white zinc corrosion or red ferrous corrosion.

REPORT

**COMPILED BY** 

REPORT APPROVED BY

G B Withers

G B Withers Corrosion Science Technician

Corrosion Science Technician

TESTS MARKED "NOT UKAS ACCREDITED" IN THIS REPORT/CERTIFICATE ARE NOT INCLUDED IN THE UKAS ACCREDITATION SCHEDULE FOR OUR LABORATORY TESTS MARKED "SC" HAVE BEEN SUBCONTRACTED. RESULTS IN THIS REPORT RELATE ONLY TO THE ITEMS TESTED OPINIONS AND INTERPRETATIONS EXPRESSED HEREIN ARE OUTSIDE THE SCOPE OF UKAS ACCREDITATION. THIS TEST REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL, WITHOUT WRITTEN APPROVAL OF THE LABORATORY