

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830
Issue date: 12/03/2024 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : STAINLESS STEEL SPRAY 500ML
Product code : 000769097288
Type of product : Paint
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Use of the substance/mixture : Spraying paint (spray can)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Specialised Aerosols Ltd
Carr Green Lane
Mapplewell
Barnsley, South Yorkshire
T 01226 387 101

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Specific target organ toxicity – Repeated exposure, Category 2 H373
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause damage to organs through prolonged or repeated exposure.
May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Contains	: n-butyl acetate; 1-methoxypropan-2-ol; Chromium; Acetone
Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, eye protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F. P501 - Dispose of contents/ container in accordance with local regulations.
EUH-statements	: EUH208 - Contains Nickel. May produce an allergic reaction. EUH066 - Repeated exposure may cause skin dryness or cracking.
Child-resistant fastening	: Not applicable
Tactile warning	: Applicable

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) substance with national workplace exposure limit(s) (BE, CZ, GB, GR, HR) (Note K)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6	24.9 – 50	Flam. Gas 1A, H220 Press. Gas
Acetone substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	24.9 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
1-methoxypropan-2-ol substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylene (mixture of isomers) substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	5 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
n-butyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, IS, MK, RS, CH); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066
Chromium substance with national workplace exposure limit(s) (AT, BE, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, NL, PL, PT, SE, SI, SK, AL, IS, CH); substance with a Community workplace exposure limit	CAS-No.: 7440-47-3 EC-No.: 231-157-5	1 – 5	STOT RE 1, H372 Aquatic Chronic 4, H413
Ethylbenzene substance with national workplace exposure limit(s) (AT, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	0.5 – 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Nickel substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, EE, ES, FI, FR, GB, HR, HU, IE, LT, LV, PL, PT, SE, SI, IS); substance with a Community workplace exposure limit (Note S)(Note 7)	CAS-No.: 7440-02-0 EC-No.: 231-111-4 EC Index-No.: 028-002-00-7	0.5 – 1	Skin Sens. 1, H317 Carc. 2, H351 STOT RE 1, H372
Manganese substance with national workplace exposure limit(s) (AT, BE, CZ, DE, DK, EE, ES, FI, HR, HU, IE, LV, NL, PL, PT, SE, SI, SK, IS, NO, MK, CH); substance with a Community workplace exposure limit	CAS-No.: 7439-96-5 EC-No.: 231-105-1	0.2 – 0.3	Not classified
Cobalt substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, GB, GR, HR, HU, IE, LV, NL, PL, PT, RO, SE, SK, IS, CH)	CAS-No.: 7440-48-4 EC-No.: 231-158-0 EC Index-No.: 027-001-00-9	0.0000001 – 0.1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 Repr. 1B, H360F STOT RE 1, H372 Aquatic Chronic 4, H413

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Quartz (SiO ₂) substance with national workplace exposure limit(s) (AT, BE, DK, EE, ES, FI, FR, HR, IE, LT, NL, PL, PT, SE, SK, NO, MK, CH); substance with a Community workplace exposure limit	CAS-No.: 14808-60-7 EC-No.: 238-878-4	0.0000001 – 0.1	Not classified
2-methoxypropanol substance with national workplace exposure limit(s) (AT, DE, DK, ES, SI, SK, IS, NO, MK, CH)	CAS-No.: 1589-47-5 EC-No.: 216-455-5 EC Index-No.: 603-106-00-0	0.0000001 – 0.1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 1B, H360D STOT SE 3, H335
Methyl methacrylate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit (Note D)	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6	0.0000001 – 0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
Butyl methacrylate substance with national workplace exposure limit(s) (DK, EE, LT, LV, PL, RO, SE, IS, NO) (Note D)	CAS-No.: 97-88-1 EC-No.: 202-615-1 EC Index-No.: 607-033-00-5 REACH-no: 01-2119486394-28	0.0000001 – 0.1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335

- Note 7: Alloys containing nickel are classified for skin sensitisation when the release rate of 0,5 µg Ni/cm²/week, as measured by the European Standard reference test method EN 1811, is exceeded.
- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.
- Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102)-P210-P403 shall apply.
- Note S: This substance may not require a label according to Article 17 (see Section 1.3 of Annex I) (Table 3).
- Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.
- Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
- Symptoms/effects after skin contact : None under normal conditions.

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
-----------------------------------	--

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials	: Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Methyl methacrylate (80-62-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methyl methacrylate
IOEL TWA	50 ppm
IOEL STEL	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
United Kingdom - Occupational Exposure Limits	
Local name	Methyl methacrylate
WEL TWA (OEL TWA)	208 mg/m³
	50 ppm
WEL STEL (OEL STEL)	416 mg/m³
	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Xylene (mixture of isomers) (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m³
	50 ppm
IOEL STEL	442 mg/m³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA)	220 mg/m³ o-,m-,p- or mixed isomers

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Xylene (mixture of isomers) (1330-20-7)	
	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers
	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m ³
	50 ppm
IOEL STEL	723 mg/m ³
	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA)	724 mg/m ³
	150 ppm
WEL STEL (OEL STEL)	966 mg/m ³
	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
1-methoxypropan-2-ol (107-98-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	1-Methoxypropanol-2
IOEL TWA	375 mg/m ³
	100 ppm
IOEL STEL	568 mg/m ³
	150 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropan-2-ol
WEL TWA (OEL TWA)	375 mg/m ³
	100 ppm

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

1-methoxypropan-2-ol (107-98-2)	
WEL STEL (OEL STEL)	560 mg/m ³ 150 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Chromium (7440-47-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Chromium metal
IOEL TWA	2 mg/m ³
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
United Kingdom - Occupational Exposure Limits	
Local name	Chromium
WEL TWA (OEL TWA)	0.5 mg/m ³ 0.5 mg/m ³ Chromium (II) compounds (as Cr) 0.5 mg/m ³ Chromium (III) compounds (as Cr)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Chromium VI
BMGV	10 µmol/mol creatinine Parameter: chromium - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Manganese (7439-96-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Manganese
IOEL TWA	0.2 mg/m ³ (inhalable fraction) 0.05 mg/m ³ (respirable fraction)
Remark	(Year of adoption 2011)
Regulatory reference	SCOEL Recommendations
Cobalt (7440-48-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Cobalt
WEL TWA (OEL TWA)	0.1 mg/m ³ and Cobalt compounds (as Co)
Remark	Carc (cobalt dichloride and sulphate)(Capable of causing cancer and/or heritable genetic damage), Sen (Capable of causing occupational asthma)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Nickel (7440-02-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Nickel metal
IOEL TWA	0.005 mg/m ³ (respirable fraction)
Remark	(Year of adoption 2011)
Regulatory reference	SCOEL Recommendations

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Nickel (7440-02-0)	
EU - Biological Limit Value (BLV)	
Local name	Nickel and nickel compounds
Regulatory reference	SCOEL List of recommended health-based BLVs and BGVs
United Kingdom - Occupational Exposure Limits	
Local name	Nickel
WEL TWA (OEL TWA)	0.1 mg/m ³ and its inorganic compounds (except nickel tetracarbonyl): water-soluble nickel compounds (as Ni) 0.5 mg/m ³ and its inorganic compounds (except nickel tetracarbonyl): nickel and water insoluble nickel compounds (as Ni)
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), Carc (Capable of causing cancer and/or heritable genetic damage (nickel oxides and sulphides)), Sen (Capable of causing occupational asthma (nickel sulphate))
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylbenzene
IOEL TWA	442 mg/m ³
	100 ppm
IOEL STEL	884 mg/m ³
	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Ethylbenzene
WEL TWA (OEL TWA)	441 mg/m ³
	100 ppm
WEL STEL (OEL STEL)	552 mg/m ³
	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Quartz (SiO2) (14808-60-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Silica crystalline (Quartz)
IOEL TWA	0.05 mg/m ³ (respirable dust)
Remark	(Year of adoption 2003)
Regulatory reference	SCOEL Recommendations
Acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Acetone (67-64-1)	
IOEL TWA	1210 mg/m ³
	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA)	1210 mg/m ³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m ³
	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Liquefied petroleum gas
WEL TWA (OEL TWA)	1750 mg/m ³
	1000 ppm
WEL STEL (OEL STEL)	2180 mg/m ³
	1250 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves					EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Silver.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -40 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: < 20.5 mm²/s
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

VOC content : 634 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Methyl methacrylate (80-62-6)	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Xylene (mixture of isomers) (1330-20-7)	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
1-methoxypropan-2-ol (107-98-2)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
Chromium (7440-47-3)	
LC50 Inhalation - Rat	> 5.41 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Manganese (7439-96-5)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure), Remarks on results: other:
LC50 Inhalation - Rat	> 5.14 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Cobalt (7440-48-4)	
LD50 oral rat	≈ 550 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 215,9 - 1140
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	≤ 0.05 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)
Nickel (7440-02-0)	
LD50 oral rat	> 9000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
Methyl methacrylate (80-62-6)	
STOT-single exposure	May cause respiratory irritation.
Butyl methacrylate (97-88-1)	
STOT-single exposure	May cause respiratory irritation.
Xylene (mixture of isomers) (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
1-methoxypropan-2-ol (107-98-2)	
STOT-single exposure	May cause drowsiness or dizziness.
2-methoxypropanol (1589-47-5)	
STOT-single exposure	May cause respiratory irritation.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Butyl methacrylate (97-88-1)	
LOAEC (inhalation, rat, gas, 90 days)	952 ppm Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEL (oral, rat, 90 days)	120 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Xylene (mixture of isomers) (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
1-methoxypropan-2-ol (107-98-2)	
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Chromium (7440-47-3)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.0044 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Cobalt (7440-48-4)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.31 mg/l air Animal: rat
NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Nickel (7440-02-0)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.004 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
Aspiration hazard	: Not classified
STAINLESS STEEL SPRAY 500ML	
Vaporizer	Aerosol
Viscosity, kinematic	< 20.5 mm²/s
Not able to form a pool	Yes
Methyl methacrylate (80-62-6)	
Viscosity, kinematic	0.561 mm²/s
Butyl methacrylate (97-88-1)	
Viscosity, kinematic	1.06 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)' Remarks on result: 'other:'

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

1-methoxypropan-2-ol (107-98-2)

Viscosity, kinematic	1.848 mm²/s
----------------------	-------------

Ethylbenzene (100-41-4)

Viscosity, kinematic	0.6 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)' Remarks on result: 'other:'
----------------------	---

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Methyl methacrylate (80-62-6)

LC50 - Fish [1]	> 79 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	69 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 110 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	37 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

Butyl methacrylate (97-88-1)

LC50 - Fish [1]	11 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	5.57 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	32 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	31.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Xylene (mixture of isomers) (1330-20-7)

EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

n-butyl acetate (123-86-4)

EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

1-methoxypropan-2-ol (107-98-2)

EC50 - Other aquatic organisms [1]	2954 mg/l Test organisms (species): other aquatic crustacea:
------------------------------------	--

Chromium (7440-47-3)

EC50 - Crustacea [1]	13.1 – 14.7 mg/l Test organisms (species): Daphnia magna
----------------------	--

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Manganese (7439-96-5)	
LC50 - Fish [1]	> 3.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1.6 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	2.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '8 d'
Cobalt (7440-48-4)	
EC50 - Crustacea [1]	> 890 µg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	5.89 mg/l Test organisms (species): Daphnia magna
Acetone (67-64-1)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
12.2. Persistence and degradability	
STAINLESS STEEL SPRAY 500ML	
Persistence and degradability	Not rapidly degradable
Methyl methacrylate (80-62-6)	
Persistence and degradability	Not rapidly degradable
Butyl methacrylate (97-88-1)	
Persistence and degradability	Not rapidly degradable
Xylene (mixture of isomers) (1330-20-7)	
Persistence and degradability	Not rapidly degradable
n-butyl acetate (123-86-4)	
Persistence and degradability	Not rapidly degradable
1-methoxypropan-2-ol (107-98-2)	
Persistence and degradability	Not rapidly degradable
2-methoxypropanol (1589-47-5)	
Persistence and degradability	Not rapidly degradable
Chromium (7440-47-3)	
Persistence and degradability	Not rapidly degradable
Manganese (7439-96-5)	
Persistence and degradability	Not rapidly degradable
Cobalt (7440-48-4)	
Persistence and degradability	Not rapidly degradable
Nickel (7440-02-0)	
Persistence and degradability	Not rapidly degradable

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Ethylbenzene (100-41-4)	
Persistence and degradability	Not rapidly degradable
Quartz (SiO ₂) (14808-60-7)	
Persistence and degradability	Not rapidly degradable
Acetone (67-64-1)	
Persistence and degradability	Not rapidly degradable
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
HP Code	: HP3 - "Flammable:" <ul style="list-style-type: none">– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
	HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
	HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.






SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains substance(s) listed on the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items: Nickel powder (7440-02-0)

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

VOC Directive (2004/42)

VOC content : 634 g/l

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Abbreviations and acronyms:	
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Nickel. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

STAINLESS STEEL SPRAY 500ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Full text of H- and EUH-statements:	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Muta. 2	Germ cell mutagenicity, Category 2
Press. Gas	Gases under pressure
Repr. 1B	Reproductive toxicity, Category 1B
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.