

# Biscuit Jointer LNF 20 in the T-MAX



ref.no.: 915601

EAN: 4032689136042

Transport and storage box T-MAX



#### Technical data

Cutting depth	11/16 Inch
Cutting tool Ø	3 15/16 Inch
Tilt range	0 - 90 °
Nominal No. of strokes – no load	9800 1/min
Nominal power input	1.0 hp
Weight	7.1 lbs
Universal motor	230 V / 50 Hz


#### **Delivery specification**

1 Disk cutter, TCT, 100 x 4 x 22 mm (3 15/16 x 3/16 x 7/8 in.), 6 teeth; Ref. No. 076905

- 1 Ejection pipe; Ref. No. 076954
- 1 Hose connector; Ref. No. 076955
- 1 Dust bag; Ref. No. 076956
- 1 Screwdriver for recessed-head screws; Ref. No. 093283
- 1 Face pin spanner; Ref. No. 093119
- 1 Mains cable 4 m (13.1 ft); Ref. No. 076953



### examples for usage



Mitred joints with the LNF 20.



Groove height adjustment via revolving depth control turret or via scale.



Available as a special accessory for the LNF 20: Pitch pocket cutter, Ref. No. 091793



The LNF 20 is supplied in the practical T-MAX.



### Applications

- , Cutting slots for biscuits
- , Cutting slots for wood patches
- , Compatible materials include solid wood, board and carcass materials

#### Advantages

- The on/off switch is easily and conveniently operated with your thumb for right-handed and left-handed users.
- With above average 750 watt (1 hp) rating for professional continuous use.
- , Double column guide for height adjustment ensures exact, torsion-free adjustment.

#### Description

Now with extra features... and all conveniently integrated in the MAFELL-MAX. Ideal for the biscuit jointing fanatics amongst you!

The tilt stop can be fixed with detents of 0°, 22.5°, 45°, and 67.5° up to 90°.

Torsion-free cast angle stop and height adjustment make your work easier while 2 sturdy adjusting bolts keep your setting constant even after your 100th cut.

All you need is "on board" in the MAFELL-MAX: practical containers for your dowels, space for the optional pitch pocket cutter, anti-slip mat and of course your LNF 20.



# Accessories / Tools

#### Disk cutter

100 x 4 x 22 mm (3 15/16 x 3/16 x 7/8 in.), 6 teeth, TCT

### Perspex base plate

for use with the pitch pocket cutter

Pitch pocket cutter 100 x 8 x 22 mm (3 15/16 x 5/16 x 7/8 in.), 2 teeth, TCT

Anti-slip mats 2 pieces



#### contact

MAFELL AG

Beffendorfer Straße 4 D-78727 Oberndorf / Neckar Germany Tel.: +49 7423 / 812-114 Fax: +49 7423 812-102 Email: export@mafell.de