

## SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/3

### THE WORKS ULTRA CUTTING OIL LIQUID

Revision Revision date 2016-01-22

SECTION 1: Identification of the substance/mixture and of the company/undertaking
---

#### 1.1. Product identifier

**Address** 

Product name THE WORKS ULTRA CUTTING OIL LIQUID

#### 1.3. Details of the supplier of the safety data sheet

STEVENS INDUSTRIAL SERVICES (SIS) LTD Company

Unit 7

Hatfield Way

South Church Enterprise Park

Bishop Auckland

DL14 6XF

Web www.stevens-sis.co.uk

**Telephone** 01388 772233 01388 772263 Fax

**Email** sales@stevens-sis.co.uk Email address of the sales@stevens-sis.co.uk competent person

#### 1.4. Emergency telephone number

Emergency telephone number 01388 772233

Mon - Fri 9.00 am - 5.00pm

#### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

_		A. 10 (1	
2.1	l.1	Classification -	

1999/45/EC

N; R50/53 R64-66

Symbols: N: Dangerous for the environment.

Main hazards

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause harm to breastfed babies. Repeated exposure may cause skin dryness or cracking.

2.1.2. Classification - EC

1272/2008

Lact.: H362; Aquatic Chronic 1: H410;

### 2.2. Label elements

#### Hazard pictograms



Signal Word

Warning

**Hazard Statement** 

Lact.: H362 - May cause harm to breast-fed children.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

**Precautionary Statement:** 

Prevention

P201 - Obtain special instructions before use.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P263 - Avoid contact during pregnancy/while nursing.

P264 - Wash thoroughly after handling.

## THE WORKS ULTRA CUTTING OIL LIQUID

Revision 1
Revision date 2016-01-22

2.2. Label elements

P270 - Do no eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

Precautionary Statement:

P308+P313 - IF exposed or concerned: Get medical advice/attention.

Response

P391 - Collect spillage.

Precautionary Statement: Disposal

P501 - Dispose of contents/container to

\_\_\_\_

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
alkanes, C14-17, chloro	602-095-00-X	85535-85-9	287-477-0		20 - 30%	R64 R66 N; R50/53	

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc.	Classification	M-factor.
				Number	(%w/w)		
alkanes, C14-17, chloro	602-095-00-X	85535-85-9	287-477-0		20 - 30%	Lact.: H362; Aquatic Acute 1:	
						H400; Aquatic Chronic 1:	
						H410;	

### SECTION 4: First aid measures

#### **SECTION 5: Firefighting measures**

#### SECTION 6: Accidental release measures

### SECTION 7: Handling and storage

#### SECTION 8: Exposure controls/personal protection

### SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance = Liquid/Liquid

## SECTION 10: Stability and reactivity

### SECTION 11: Toxicological information

### SECTION 12: Ecological information



# THE WORKS ULTRA CUTTING OIL LIQUID

Revision 1 Revision date 2016-01-22

## **SECTION 13: Disposal considerations**

## **SECTION 14: Transport information**

## SECTION 15: Regulatory information

## **SECTION 16: Other information**

#### Other information

Revision	This document differs from the previous version in the following areas:. 2 - 2.1. Classification of the substance or mixture. 2 - 2.1.2. Classification - EC 1272/2008.						
	2 - Hazard pictograms.						
	2 - Signal Word.						
	2 - Precautionary Statement: Prevention.						
	2 - Precautionary Statement: Response.						
	2 - Precautionary Statement: Disposal.						
	9 - 9.1. Information on basic physical and chemical properties (Appearance).						
Text of risk phrases in Section	R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic						
3	environment.						
	R64 - May cause harm to breastfed babies.						
	R66 - Repeated exposure may cause skin dryness or cracking.						
Text of Hazard Statements in	EUH066 - Repeated exposure may cause skin dryness or cracking.						
Section 3	Lact.: H362 - May cause harm to breast-fed children.						
	Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.						

