

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Husqvarna 2-Stroke Oil Guard

Registration number

None. **Synonyms**

Product code 544 97 65-01 (1L), 544 97 65-02 (0,1L)

29-May-2015 Issue date

01 Version number **Revision date** Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses 2-Stroke oil

Uses advised against Use in accordance with supplier's recommendations.

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier Husqvarna AB Address Drottninggatan 2 **Telephone** +46 (0)36-14 65 00 Contact person **Accessory Department** E-mail sds.info@husqvarna.se

1.4. Emergency telephone

+1-760-476-3961 (Access code 333721)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary

Physical hazards Not classified for physical hazards. **Health hazards** Not classified for health hazards.

Environmental hazards Not classified for hazards to the environment.

Specific hazards May be irritating to the skin. May cause eye irritation on direct contact. May form vapours or oil

> mists during mechanical action or at elevated temperatures which may be irritating to respiratory tract. Vapours may cause drowsiness and dizziness. Prolonged exposure to oil mist may cause pulmonary disease such as chronic inflammation. Prolonged and repeated contact with used oil

may cause serious skin diseases, such as dermatitis and skin cancer.

Main symptoms May cause redness and pain. Defatting of the skin. Dermatitis. May cause eye irritation on direct

> contact. Ingestion may cause irritation and malaise. Vapours may cause drowsiness and dizziness. In high concentrations, mists/vapors may irritate throat and respiratory system and

cause coughing.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

None. Hazard pictograms Signal word None

The mixture does not meet the criteria for classification. **Hazard statements**

Precautionary statements

Not assigned. Prevention Response Not assigned. Storage Not assigned.

Husqvarna 2-Stroke Oil Guard SDS UK **Disposal** Not assigned.

Supplemental label information EUH210 - Safety data sheet available on request.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Highly refined mineral oil (DMSO-extract < 3% IP 346)		> 50	-	-	-	
Classification:	DSD:	-				
	CLP:	-				
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			64742-47-8 265-149-8	-	649-422-00-2	
Classification:	DSD:	Xn;R65, R66				
	CLP:	Asp. Tox. 1;H30)4			
Hydrocarbyl amine		1 - 5	Polymer	-	-	
Classification:	DSD:	R52/53	-			

List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008. DSD: Directive 67/548/EEC.

#: This substance has been assigned Community workplace exposure limit(s).

CLP: Aquatic Chronic 3;H412

#. This substance has been assigned Community workplace exposure limit(s).

Composition commentsThe full text for all R- and H-phrases is displayed in section 16. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Call a physician if symptoms develop or

persist.

Skin contact Immediately remove contaminated clothing. Wash with soap and water. Continue to rinse for at

least 15 minutes. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions. If high pressure injection under the skin occurs, always seek

medical attention.

Eye contact Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open

eyelids wide apart. If irritation persists: Continue flushing during transport to hospital. Take along

these instructions.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get immediate

medical attention.

4.2. Most important symptoms and effects, both acute and

delayed

May cause redness and pain. Defatting of the skin. Dermatitis. May cause eye irritation on direct contact. Ingestion may cause irritation and malaise. Vapours may cause drowsiness and dizziness. In high concentrations, mists/vapors may irritate throat and respiratory system and

cause coughing.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Symptoms may be delayed. HIGH PRESSURE SKIN INJECTION: Physician must be familiar with local procedures for treatment of this type of wound; incision, irrigation, removal of all necrotic tissue and open wound dressing.

SECTION 5: Firefighting measures

General fire hazards Heating may generate vapors which may form explosive vapor/air mixtures. Material will float and

can be re-ignited on surface of water.

Husqvarna 2-Stroke Oil Guard SDS UK

5.1. Extinguishing media

Suitable extinguishing

media

Foam. Dry powder. Carbon dioxide (CO2). Water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture By heating and fire, irritating vapours/gases may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in

the workplace.

Special fire fighting

procedures

Move container from fire area if it can be done without risk. Use water spray to cool unopened containers. Cool containers exposed to flames with water until well after the fire is out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). In case of spills, beware of slippery floors and surfaces. Avoid breathing mist or vapour. Avoid contact with skin and eyes. Wear protective clothing as described in section 8 of this safety data sheet.

For emergency responders

Keep unnecessary personnel away. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not allow to enter drains, sewers or watercourses. Environmental manager must be informed of all major releases.

6.3. Methods and material for containment and cleaning up

Remove sources of ignition. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Large Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Wash area with soap and water.

Small Spills: Absorb spillage with non-combustible, absorbent material. Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas. Avoid inhalation of oil mist and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Wash contaminated clothing before reuse. Be aware of potential for surfaces to become slippery. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from ignition, flame and heat sources. Keep container tightly closed. Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Store locked up.

7.3. Specific end use(s) 2-Stroke oil.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits noted for ingredient(s).

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no-effect level (DNEL) Not available. Predicted no effect

concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation and minimise the risk of inhalation of vapours and oil mist. Use explosion-proof equipment. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

General information

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Risk of contact: Wear safety glasses with side shields (or goggles).

Skin protection

Husqvarna 2-Stroke Oil Guard SDS UK

906396 Version #: 01 Revision date: -Issue date: 29-May-2015

Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid may - Hand protection

penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the

glove supplier.

- Other Wear appropriate clothing to prevent repeated or prolonged skin contact.

In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with Respiratory protection

combination filter (type A2/P2) can be used. Wear air-supplied mask in confined areas. Seek

advice from local supervisor.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Always observe good personal hygiene measures, such as washing after handling the material Hygiene measures

> and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Private clothes and working clothes should be kept

separately.

Environmental exposure

controls

Environmental manager must be informed of all major spillages.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Colour Orange. Odour Solvent. **Odour threshold** Not available. pН Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

89.0 °C (192.2 °F) ISO 2719 Flash point

Not available. **Evaporation rate** Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

< 0.01 kPa Vapour pressure Not available. Vapour density

Relative density 0.871 Solubility(ies) Negligible.

Partition coefficient Log Kow: >3 (Estimated).

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature**

45.17 mm2/s (40 °C) **Viscosity**

Explosive properties Not explosive. Oxidizing properties Not oxidising.

9.2. Other information

871.30 kg/m3 ISO 12185 Density

SECTION 10: Stability and reactivity

The product is non-reactive under normal conditions of use, storage and transport. 10.1. Reactivity

10.2. Chemical stability Material is stable under normal conditions. Hazardous polymerisation does not occur. 10.3. Possibility of hazardous

reactions

Heat, sparks, flames, elevated temperatures. Contact with incompatible materials. 10.4. Conditions to avoid

10.5. Incompatible materials Strong oxidising agents. Strong acids.

By heating and fire, irritating vapours/gases may be formed. Carbon oxides. 10.6. Hazardous

decomposition products

Husqvarna 2-Stroke Oil Guard SDS UK

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Vapours may cause drowsiness and dizziness. Breathing of high concentrations may cause

dizziness, light-headedness, headache, nausea and loss of co-ordination. Continued inhalation

may result in unconsciousness.

Skin contact May be irritating to the skin. Prolonged or repeated contact may dry skin and cause dermatitis.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Ingestion may cause irritation and malaise. Ingestion may result in vomiting; aspiration (breathing)

of vomitus into lungs must be avoided as even small quantities may result in aspiration

pneumonitis.

Symptoms May cause redness and pain. Defatting of the skin. Dermatitis. May cause eye irritation on direct

contact. Ingestion may cause irritation and malaise. Vapours may cause drowsiness and dizziness. In high concentrations, mists/vapors may irritate throat and respiratory system and

cause coughing.

11.1. Information on toxicological effects

Acute toxicity May irritate and cause stomach pain, vomiting, diarrhoea and nausea. Human evidence indicates

that the product has very low acute oral, dermal or inhalation toxicity. However, it can produce severe injury if taken into the lung as a liquid, and there may be profound central nervous system

depression following prolonged exposure to high levels of vapour.

Skin corrosion/irritation May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to

discomfort and dermatitis.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation No data available.

Skin sensitisation No data available.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classified.

Reproductive toxicity No data available.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

No data available.

Aspiration hazard Not classified, however droplets of the product may be aspirated into the lungs through ingestion

or vomiting and may cause a serious chemical pneumonia.

Mixture versus substance

information

Not available.

Other information Prolonged and repeated contact with used oil may cause serious skin diseases, such as

dermatitis and skin cancer.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and

degradability

Expected to biodegrade slowly.

12.3. Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient n-octanol/water (log Kow)

Log Kow: >3 (Estimated).

Bioconcentration factor (BCF)

Not available.

12.4. Mobility in soil The product adsorbs strongly to soil.

Mobility in general The product is insoluble in water. It will spread on the water surface while some of the components

will eventually sediment in water systems. The volatile components of the product will spread in the

atmosphere.

12.5. Results of PBT

and vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effectsOil spills are generally hazardous to the environment.

Husqvarna 2-Stroke Oil Guard SDS UK

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions)

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. The Waste code should be assigned in discussion between the user, the producer and the waste

EU waste code disposal company.

Disposal methods/information Dispose in accordance with all applicable regulations. This material and/or its container must be

disposed of as hazardous waste.

SECTION 14: Transport information

ADR

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

ADN

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Code

Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not applicable.

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Not listed.

Husqvarna 2-Stroke Oil Guard SDS UK

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances

Not listed.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS 64742-47-8)

Directive 94/33/EC on the protection of young people at work

Not listed.

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws.

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations 15.2. Chemical safety Follow national regulation for work with chemical agents. No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

DNEL: Derived No-Effect Level.

PNEC: Predicted No-Effect Concentration.
PBT: Persistent, bioaccumulative and toxic.
vPvB: Very Persistent and very Bioaccumulative.

References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS) ESIS (European chemical Substances Information System)

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if

available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Husqvarna 2-Stroke Oil Guard SDS UK