

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SPIT MULTI-MAX PLUS PART A

Resin.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

1.3. Details of the supplier of the safety data sheet

Supplier

SPIT 150 avenue de Lyon 26500 BOURG-LES-VALENCE France Tel: 0 810 102 102 Fax: 0 810 432 432 email: msds-reach@spit.com

1.4. Emergency telephone number

Emergency telephone 112 24/24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)		
Physical hazards	Not Classified	
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	
Environmental hazards	Aquatic Chronic 3 - H412	

2.2. Label elements

Hazard pictograms



Signal word	Warning
Hazard statements	EUH208 Contains 2,2'-[(4-METHYLPHENYL)IMINO]BISETHANOL. May produce an allergic reaction. H315 Causes skin irritation. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements	 P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/ container in accordance with national regulations.
Supplementary precautionary statements	 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P403+P235 Store in a well-ventilated place. Keep cool.
Labelling notes	The product is not flammable. On basis of test data. UN Test N.1 and ASTM D4359-90

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

VINYL TOLUENE		10-20%
CAS number: 25013-15-4	EC number: 246-562-2	
Classification		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		
TITANIUM DIOXIDE		>0.5 <1.0%
CAS number: 13463-67-7	EC number: 236-675-5	
Classification		
Carc. 2 - H351		
2,2'-[(4-METHYLPHENYL)IMINO	BISETHANOL	<0.5%
CAS number: 3077-12-1	EC number: 221-359-1	
Classification		
Acute Tox. 4 - H302		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		

SECTION 4: First aid measures

4.1. Description of first aid measures

Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.	
Skin contact	Wash skin thoroughly with soap and water.	
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.	
4.2. Most important symptoms	and effects, both acute and delayed	
Ingestion	May cause discomfort if swallowed.	
Skin contact	Irritating to skin.	
Eye contact	Irritating to eyes.	
4.3. Indication of any immedia	te medical attention and special treatment needed	
Notes for the doctor	No specific recommendations.	
SECTION 5: Firefighting meas	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.	
5.2. Special hazards arising from	om the substance or mixture	
Specific hazards	Not considered to be a significant hazard due to the small quantities used.	
Hazardous combustion products	Oxides of carbon.	
5.3. Advice for firefighters		
Protective actions during firefighting	Avoid breathing fire gases or vapours.	
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.	
SECTION 6: Accidental release	e measures	
6.1. Personal precautions, pro	tective equipment and emergency procedures	
Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.	
6.2. Environmental precaution	<u>S</u>	
Environmental precautions	Avoid release to the environment.	
6.3. Methods and material for containment and cleaning up		
Methods for cleaning up	Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.	
6.4. Reference to other section		
Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.	
SECTION 7: Handling and sto	rage	

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place.		
Storage class	Chemical storage.		
7.3. Specific end use(s)			
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.		
SECTION 8: Exposure contro	Is/Personal protection		
8.1. Control parameters			
Occupational exposure limits TITANIUM DIOXIDE			
Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust WEL = Workplace Exposure Limit.			
	VINYL TOLUENE (CAS: 25013-15-4)		
DNEL	Industry - Inhalation; Long term systemic effects: 37 mg/m ³ Industry - Inhalation; Long term local effects: 37 mg/m ³ REACH dossier information		
PNEC	 Fresh water; 0.0498 mg/l marine water; 0.002 mg/l Intermittent release; 0.013 mg/l STP; 1 mg/l Sediment (Freshwater); 0.684 mg/kg Sediment (Marinewater); 0.0684 mg/kg Soil; 0.133 mg/kg REACH dossier information 		
TITANIUM DIOXIDE (CAS: 13463-67-7)			
DNEL	Industry - Inhalation; Long term systemic effects: 10 mg/m ³ REACH dossier information		
PNEC	 Fresh water; 0.127 mg/l marine water; 1.0 mg/l Intermittent release; 0.61 mg/l STP; 100 mg/l Sediment (Freshwater); 1000 mg/kg Sediment (Marinewater); 100 mg/kg Soil; 100 mg/kg REACH dossier information 		

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	It is recommended that chemical-resistant, impervious gloves are worn.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Solid.
Colour	Beige.
Odour	Aromatic.
Odour threshold	Not determined.
рН	Not applicable.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	Not applicable.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.65 - 1.75 @ 20°C
Bulk density	Not applicable.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not applicable.

Explosive properties	Not applicable.		
Explosive under the influence of a flame	Not applicable.		
Oxidising properties	Not determined.		
9.2. Other information			
SECTION 10: Stability and re	activity		
10.1. Reactivity			
Reactivity	The following materials may react with the product: Organic peroxides/hydroperoxides.		
10.2. Chemical stability			
Stability	Stable at normal ambient temperatures.		
10.3. Possibility of hazardous	s reactions		
Possibility of hazardous reactions	Does not decompose when used and stored as recommended.		
10.4. Conditions to avoid			
Conditions to avoid	Iditions to avoid Avoid excessive heat for prolonged periods of time.		
10.5. Incompatible materials			
Materials to avoid	Organic peroxides/hydroperoxides.		
10.6. Hazardous decomposition products			
Hazardous decomposition products	Oxides of carbon.		
SECTION 11: Toxicological in	nformation		
11.1. Information on toxicolog	gical effects		
Acute toxicity - inhalation ATE inhalation (vapours mg/l) 79.18		
Ingestion	May cause discomfort if swallowed.		
Skin contact	Causes skin irritation.		
Eye contact	/e contact Causes eye irritation.		
Route of exposure	Skin and/or eye contact		
Medical symptoms	Irritation of eyes and mucous membranes. Skin irritation.		
Toxicological information on i	ingredients.		
	VINYL TOLUENE		
Acute toxicity -	oral		
Acute toxicity or mg/kg)	ral (LD₅₀ 2,255.0		
_	ral (LD₅₀ 2,255.0 Rat		
mg/kg)	Rat		

Acute toxicity - dermal

Acute toxicity mg/kg)	dermal (LD₅₀	4,500.0
Species		Rat
ATE dermal (I	ng/kg)	4,500.0
Acute toxicity	- inhalation	
ATE inhalation mg/l)	n (vapours	11.0
Carcinogenici	ty	
IARC carcino	genicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
		TITANIUM DIOXIDE
Acute toxicity	- oral	
Acute toxicity		5,000.0
mg/kg)		
Species		Rat
Carcinogenici	<u>ty</u>	
IARC carcino	genicity	IARC Group 2B Possibly carcinogenic to humans.
SECTION 12: Ecological in	formation	
<u>12.1. Toxicity</u> Ecological information on ir	ngredients.	
		VINYL TOLUENE
Acute aquatic	toxicity	
Acute toxicity	- fish	LC50, 96 hours: 23.4 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity invertebrates	- aquatic	EC₅₀, 48 hours: 1.3 mg/l, Daphnia magna
Acute toxicity plants	- aquatic	EC₅₀, 72 hours: 2.6 mg/l, Selenastrum capricornutum
		TITANIUM DIOXIDE
Acute aquatic	toxicity	
Acute toxicity	- fish	LC0, >: 1000 mg/l, Leuciscus idus (Golden orfe) REACH dossier information
Acute toxicity invertebrates	- aquatic	NOEC, > 48 hours: 3 mg/l, Daphnia magna REACH dossier information
Acute toxicity microorganisr		EC₅₀, > 3 hours: 1000 mg/l, Activated sludge REACH dossier information
12.2. Persistence and degr	adability	
12.3. Bioaccumulative pote	ntial	
Bioaccumulative potential	No data a	available on bioaccumulation.
Partition coefficient	Not deter	rmined.

Ecological information on ingredients.

VINYL TOLUENE

Partition coeffic	ient log Pow: 3.36	
12.4. Mobility in soil		
Mobility	Not applicable.	
12.5. Results of PBT and vPv	vB assessment	
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.	
12.6. Other adverse effects		
Other adverse effects	Not applicable.	
SECTION 13: Disposal consi	iderations	
13.1. Waste treatment metho	bds	
General information	Dispose of waste product or used containers in accordance with local regulations	
Disposal methods	Dispose of waste via a licensed waste disposal contractor.	
Waste class	The waste code classification is to be carried out according to the European Waste Catalogue (EWC).	
SECTION 14: Transport information		
General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).	
14.1. UN number		
Not applicable.		
14.2 LIN proper chipping ner		

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (E	U) No 2015/830
-------------------	----------------

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	The product is not flammable. On basis of test data. UN Test N.1 and ASTM D4359-90
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	29/07/2022
Version number	3.002
Supersedes date	23/10/2020
SDS number	21486
Hazard statements in full	 H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H351 Suspected of causing cancer. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains 2,2'-[(4-METHYLPHENYL)IMINO]BISETHANOL. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.