

Rotary Hammer

HR2630

800 W • SDS-PLUS • 26 mm • 2.4 J

Professional three-mode rotary hammer

Efficient rotary hammer compatible with SDS-PLUS bits. Suitable for impact and unstressed drilling, plus chipping. Motor capacity of 800 W and speed can be adjusted between 0 and 1 200 min⁻¹ from a switch. Impact energy of 2.4 J and optimal drilling range of 8 – 18 mm in concrete. Max. drilling capacity of 26 mm in concrete.



Technical specifications

Continuous Input Power	800 W
No load speed	0 - 1200 min ⁻¹
Impacts per Minute (IPM)	0 - 4600 min ⁻¹
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Concrete	26 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	8 - 18 mm
Impact Energy	2,4 J
Power Supply Cord	2,5 m
Drilling diameter with TCT core bit	68 mm
Sound Power Level (L _{WA})	101 dB(A)
Sound Pressure Level (L _{pA})	90 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²

User benefits

- The rubber coating on the handle ensures a firm working grip
- Torque limiter stops rotation if bit jams for increased operator safety and enhanced motor protection
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Variable speed trigger allows the user to adjust discharge rate
- Depth gauge for increased drilling consistency

EAN 0088381687300

Link to product - www.makita.com



Related products

Optional AC

193472-7

Dust extraction set Ø 25 / 31 mm



331886-4

Depth Gauge

821550-0

Makpac case (2)



821775-6

Carrying Case



824914-7

Plastic Carrying Case



837651-4

MakPac (2) Inlay



Other

[User manual](#)

[Parts drawing](#)