



# TruTool TKF 700

Technical data

**TruTool TKF 700 30°  
bevel angle****TruTool TKF 700  
37.5° bevel angle****TruTool TKF 700 45°  
bevel angle****MAXIMUM CHAMFER LENGTHS  
/ MAXIMUM CHAMFER HEIGHTS**

Maximum chamfer length, steel 400 N/mm <sup>2</sup>	7 mm	7 mm	7 mm
Maximum chamfer height, steel 400 N/mm <sup>2</sup>	5 mm	5 mm	5 mm
Maximum chamfer length, steel 600 N/mm <sup>2</sup>	5.7 mm	5.7 mm	5.7 mm
Maximum chamfer height, steel 600 N/mm <sup>2</sup>	4 mm	4 mm	4 mm
Maximum chamfer length, steel 800 N/mm <sup>2</sup>	4 mm	4 mm	4 mm
Maximum chamfer height, steel 800 N/mm <sup>2</sup>	3 mm	3 mm	3 mm

**RADII**

Smallest radius	40 mm	40 mm	40 mm
-----------------	-------	-------	-------

**GENERAL**

Working speed (max.)	1.5 m/min	1.5 m/min	1.5 m/min
Nominal power consumption	1700 W	1700 W	1700 W
Sheet thickness	1 mm - 20 mm	1 mm - 20 mm	1 mm - 20 mm

**DIMENSIONS**

Length	342 mm	342 mm	342 mm
Height	240 mm	240 mm	240 mm

**WEIGHT**

Weight	5.3 kg	5.3 kg	5.3 kg
--------	--------	--------	--------

Subject to changes. The details in our offer and order confirmation are definitive.